

Made In Japan صنــع باليـابــان

a later the second		
a later the second	-	
a later the second		
a later the second		
a Sette Tarline Care		
a later the second		
a Sette Tarline Care		
a Sette Tarline Care		
alah Tahun Cara		
alah Tahun Cara		
a fait the state of the second		
a sale to find the company		
a sale that the second		
and and the Construction		
A STATE OF		
A STATE OF		
STATISTICS IN A STATISTICS		
State and a state of the state		
いいえ 一般にある 生き なままになって		
AND DESCRIPTION OF THE OWNER OF T		

For Agriculture&Garben

Hoping for an abundant crop ...

HIDELS PUMPS

SE-XK Series



SE-50XK, SE-80XK

Kerosene Engine Pumps

- Highly effective mechanical seal made with special carbon ceramics provides extra durability.
- Entire unit is protected by sturdy rollover pipe frame.
- Strong and lightweight die-cast aluminum pump.

Applications

- Sprinkling for field irrigation.
- Irrigation of paddy fields.
- Orchard cultivation.
- Pumping water from wells.
- Feeding or draining water to/from ponds or troughs.
- Feeding or draining water on fish farms.
- Washing cattle, barns or agricultural tools.
- Feeding water into water reservoirs.

Specifications

	Model	SE-50XK	SE-80XK	
	Connection Dia	50 mm (2")	80 mm (3")	
P	Connection Thread	Outer Pipe Thread		
M	Total Head	23 m (75 ft)	26 m (85 ft)	
P	Delivery Volume	560 L/min (148 USG/min)	880 L/min (232 USG/min)	
	Max. Suction Head	8 m (26 ft)		
E	Туре	Forced Air-cooled 4-st	roke Kerosene Engine	
N	Model	Robin EY15-3DK	Robin EY20-3DK	
G	Exhaust Volume	143 cc	183 cc	

Ι	Rated Power	Rated Power	1.6 kW (2.2 PS) / 3600 rpm	2.3 kW (3.1 PS) / 3600 rpm	
N	Output	Max. Power	2.4 kW (3.3 PS) / 4000 rpm	3.2 kW (4.3 PS) / 4000 rpm	
E	Fuel		Kerosene (Gasoline for starting)		
	Fuel Tenk	Consoity	Kerosene: 2.6 L	Kerosene: 3.4 L	
	Fuel Tank Capacity		Gasoline: 0.13 L	Gasoline: 0.17 L	
	Continuous	Operating Time	Approx. 2 hrs 30 min	Approx. 3 hrs 30 min	
	Starting Method		Recoil Starter		
St	andard Acce	essories	1 Strainer, 2 Hose Couplings, 3 Hose Bands, 1 Engine Tool Set		
G	ross Weight		25 kg	34 kg	
Di	imensions		489 x 362 x 435	535 x 380 x 487	
L	LxWxH (mm)		+07 x 502 x +55	555 X 500 X 707	
Packing Unit			1		



Robin Machineries & Equipment

Tel: 000971-4-2217124 Fax: 000971-4-2234493 POBox: 5229 Dubai, UAE Email: <u>alawitra@emirates.net.ae</u> www.alawigroup.ae