



Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae

EG6500-A/EG6500D-A

- Rated power of 5000 watt, 110/220/230/240V
- Eagle commercial-grade OHV engine
- Automatic voltage regulation by AVR
- Low oil level automatic protection
- Current over current protection
- Capacious fuel tank of 25 liter, for which to run 9 hours constantly
- Frame-type safety generator support v •Wheel components are optional
- Self-starting or remote-starting is optional.



Engine model	G390F/G390FD
Engine type	Single cylinder, 4stroke, forced cooling ,OHV
Power output	8.2Kw/3600rpm
Bore×Stroke	88mm×64mm (3.5"×2.5")
Displacement	389cc
Compression ratio	8.0:1
Oil capacity	1.1L (0.29gal)
Fuel tank capacity	25L (6.6gal)
Fuel consumption	≤374g/Kw.h
Continuing time	9h
Rated frequency	50 Hz/60 Hz
Rated voltage	110V/115V/120V/220V/ 230V/240
Voltage regulator system	Automatic Voltage Regulation
Rated output	5.0Kw
Max output	5.5Kw
Power factor	1.0
Charging voltage	12V(DC)
Charging current	8.3A(DC)
Starting system	Recoil start
Ignition system	Transistorized magneto ignition
Noise	≤76dB(A)
Dimension	675×540×540 (26.6"×21.3"×21.3")
Net weight	77Kg (169.8lb)

Options:

Fuel tank, recoil starter colors and types

•DC 12V output

•Voltage meter indicator type or digital type

•Wheel kit

•Intelligent Self-start or remote start